Hose And Duct Australia Pty Ltd 0455 904 883

- e simon@hoseandduct.com.au
- w www.hoseandduct.com.au
- PO Box 1450 Cleveland 4163



Two-eye Hose Restraint

Wire Aid part no	Size range (mm) and colour code	Lattice weave	Overall length (mm)	Approx breaking strength (kg)
Galvanised				
HR2E01	8-14	12 x 3	440	1500
HR2E02	14-20	12 x 3	500	2100
HR2E03	20-30	12 x 2	770	3000
HR2E04	30-40	12 x 2	1000	5400
HR2E05	40-50	12 x 2	1070	5400
HR2E06	50-60	12 x 2	1360	7500
HR2E07	60-70	12 x 2	1450	7500
HR2E08	70-85	12 x 2	1500	7500
HR2E09	85-100	12 x 2	1780	10000
HR2E10	100-120	12 x 2	1880	10000
HR2E11	120-140	16 x 2	2400	14000
HR2E12	140-180	16 x 2	2440	14000
HR2E13	180-240	16 x 2	3000	14000

The Wire Aid two-eye hose restraints standard range are made with the following materials:

- Wire: Galvanised
- · Ferrules: Aluminium
- · Thimbles: Stainless Steel
- Leg Protection: Spiral Guards (Colour Coded)

The Wire Aid standard range can be varied with 316 stainless steel wire and thimbles and 316 stainless steel or copper ferrules at your request.

There are a number of variations to this standard range with the most popular being the:




Smooth-ended Two-eye Hose Restraint

- Reverse woven to allow for smoother finish where no ferrules are required to hold the wires together at the end point of the restraint
- No ends protruding means safer to handle and fit
- Same properties and breaking strains as our standard two-eye restraints.

Thermo Plastic Sleeve (TPS) Hose Restraint*





- Same properties and breaking strains as our standard two-eye restraints.
- * Thermo Plastic Sleeve limits inspection of the wire underneath for wear and tear. Please check with Wire Aid if the inspection limitation of this product makes it the most suitable option for your safety needs.

Internal Hose Restraint

. Consists of a wire rope running inside the length of the hose and attached internally

to the couplings at each end of the hose

 It is used in addition to external hose restraints for extra safety. For use with clean air hoses.

Wire Aid part no	Size range (mtr)	Approx breaking strength (kg)
Galvanised		
HRIN97	0-10	1800
HRIN98	10-20	1800

